



aerotec

Aerotec

\$460.00



Νοαίααδοία εηηρεαεοαογ. Οίρεαεüíεε α³çαεί "íεααíñüεα δαεεγ", íααοίíεεε. Αíáδαιάοαεοεαί³ñòü Å++. Οίεíá / οáíεí, ñαííá³ααíñòεεá, àáοíδáñòáδò, áíδèéíδíç³εíá ííεδèòòγ, δαείíáδ 24 á., í³ááεùáíá δáíεíá³ááá-à, á³áδío³εüíá ííεδèòòγ δáíεííáí³íεεá, çíáíøáíεε δ³ááíü øóío, εááεíçéííá íáδááíγ íáíáεü, íðεοíááíεε LED áεñíεáε. Ξí³çàοíð, δοίεογ "Super Cool 17C", δεδèε δáæèì εííοíδòííáí ñío, δáæèì Óοδái, δ³εüδòè High Density δà Cold Catal³st, δáæèì ÍÄÉ Favorite Mode. Νò³εεá δíáíòà íà íá³áδ³á áí - 15°C.

ÒÁÓí²xí² ÕÀÐÀÊÕÀÐËÑÕÈÈÈ

Áíοδδ³øíé áεíê

Íáçáà ííááε³: MSMA-09HRDN1-Q ION

Áεáεδδíæεáεáíγ, Á/Ãö/Õ: 220/50/1

Ííδóæí³ñòü, éÃò

Íοíεíáæáíγ: 0,4 - 2.64

Íááδ³á: 0,5 - 2.93

Ííδóæí³ñòü ñííæεááíγ, éÃò

Íοíεíáæáíγ: 0,1 - 1,24

Íááδ³ááíγ: 0,12 - 1,24

Àèòðàòè ïîá³ððÿ, î?/âîä.: 270 - 490

Ð³âáíü øóíó, äÁ: 29 - 39

Ãàáàðèèó³ ðíçì³ðè (ØõÃõÃ), ì

Áàç óìàèíâèè: 715x285x205

Ã óìàèíâõ³: 780x360x285

Ãàãà, èã

Ãàãà íàòòí: 7

Çàãàèüíà áàãà: 9

Çíáí³øíé áéíè

Òèí èííðãñîðà: Inverter

Éííðãñîð: GMCC ROTARY

Óðáíí

Òèí òðáííó: R410A

Ãàãà òðáííó, èã: 0.8

Áèáèòðíæèáèáííÿ, Ã/Ãõ/Õ: 220/50/1

Àèòðàòè ïîá³ððÿ, î?/âîä.: 1800

Ð³âáíü øóíó, äÁ: 55

Ã³áíàòð òðóá, ì

Äèÿ ð³àèèè: 6.35(1/4")

Ãàçíâà: 9.52(3/8")

Ìàèñ. áíâæèíà ìàã³ñòðàè³, ì: 25

Ìàèñ. ïáðáíàä àèñîò, ì: 10

Ãàáàðèèó³ ðíçì³ðè (ØõÃõÃ), ì

Áàç óìàèíâèè: 700x555x300

Ã óìàèíâõ³: 900x585x345

Ãàãà, èã

Ãàãà íàòòí: 25

Çàääëüía àääà: 28

Ä³äiäçíí ðíáí÷èõ çíáí³øí³õ òàíiäðàòóð:

Ðåæèì íðíëíäæáíý: (-15) – (+50)°Ñ

Ðåæèì íá³äð³áo: (-15) – (+30)°Ñ

Ãðáíò³ý 2 ðíèè.

[Vendor Information](#)